

RED200 - Elevator Ø 300 mm - 600 mm

For inspections with pipe diameters of more than DN 300 up to DN 600 your ROVION®-system can be upgraded with an optional elevator. This elevator can automatically be moved up or down through the control panel thus offering perfect centering of the camera unit inside the piping system in each and every inspection situation.

TECHNICAL DATA - RED200	
Nominal pipe widths	DN 300 up to DN 600
Pressure tightness	up to max. 1 bar
Drive	motor-driven
Optional accessories	auxiliary lights RAL130, RAL200, RAL1000-RCX90, RAL1000-DSIII; camera RCX90, RAC50, PTP70II; fisheye camera DSIII
Power supply	via cable reels
Special features	-
Protection class	IP68 up to 10 m water depth
Ambient temperature range	0 °C - 40 °C
Storage temperature range	0 °C - 40 °C
Material	aluminum anodized
Dimensions (L x W x H)	retracted: 315 x 80 x 145 mm extended: 315 x 80 x 320 mm
Weight	3.2 kg



- Simple and fast mounting to / removal from the crawler
- Motor-driven
- Stepless height adjustment
- Interface for cameras and auxiliary lights
- Exclusively compatible to the RX130 crawler
- Optionally available as EX version



iPEK International GmbH · See, Gewerbepark 22 · 87477 Sulzberg · GERMANY

☎ +49 8376 921 800 📠 +49 8376 921 8021 ✉ isg_info@idexcorp.com 🌐 www.ipek.at

Issue: April 2015 – subject to changes.